

WHAT IS CLAIMED IS:

Subs
AT

5 1. An optical space transmitter comprising:
a light source for emitting a light beam modulated
according to a signal to be transmitted;
an optical system for sending out the light beam
emitted from said light source as transmission light
beam with an angle of expansion;

a temperature detector for detecting the internal
temperature of the device; and

10 a control means for changing the angle of
expansion of said transmission light beam as a function
of the temperature detected by said temperature
detector.

15 2. An optical space transmitter according to
claim 1, wherein

said control means includes an computing circuit
for determining by computation an appropriate angle of
expansion of the light beam to be transmitted on the
20 basis of the temperature detected by said temperature
detector and a drive means for driving at least part of
said optical system in the direction of the optical
axis according to the outcome of the computation of the
computing circuit.

25 3. An optical space transmitter according to
claim 1, further comprising:

a light receiving means for converting the reception signal transmitted from another device and taken into the own device so as to make the optical axis thereof agree with the optical axis of the light beam to be transmitted into an electric signal.

4. An optical space transmitter according to claim 3, further comprising:

an angle correcting means for correcting the angular displacement between the light beam to be transmitted and the received light beam.

5. An optical space transmitter according to claim 4, wherein

said angle correcting means has a tracking mirror arranged on the optical path of the light beam to be transmitted and the received light beam and an actuator for changing the angle of the tracking mirror.

6. An optical space transmitter according to claim 5, wherein

said optical system includes a beam splitter for separating the received light beam from the light beam to be transmitted and a half mirror for dividing the received light beam separated by the beam splitter into two light beams and said light receiving means includes a first photodetector for receiving one of the two

Subs
a7

SAS
a7
cl

light beams produced by said half mirror by dividing the incoming light beam and detecting it as main signal and a second photodetector for receiving the other light beam and detecting the angular displacement between the light beam to be transmitted and the received light beam, said actuator being adapted to change the angle of the tracking mirror according to the output signal of said second photodetector.

5

Tab a7